



# No Center Stop Slide On Couplings

## Joins Conduit Lengths in Difficult Situations

**NEW**

Allows flexibility of movement for fast, easy installation of conduit in tight, difficult situations.

**PATENT PENDING**  
UL LISTED FOR 3/4, 1, 2 & 4 inch  
UL514B & CSA C22.2 No. 18.3  
(other sizes pending)

Completely smooth inside diameter with smooth bottomed adjustable center screw. No sharp edges to damage wire during pull.



1. Slide coupling over end of one conduit
2. Line up 2nd conduit and mark it to allow coupling to be slid back and centered over both conduits.
3. Slide coupling back to mark.
4. Tighten  $\frac{3}{8}$ " hex head bolts and conduits are securely joined together at center of coupling.
5. Size  $\frac{1}{2}$  thru 2 inch = one bolt sizes  $2\frac{1}{2}$  and larger = 2 bolts at a 45° angle on each end

SIZE	CAT#	SIZE	CAT#
1/2"	NCSC-50EMT	2"	NCSC-200EMT
3/4"	NCSC-75EMT	2-1/2"	NCSC-250EMT
1"	NCSC-100EMT	3"	NCSC-300EMT
1-1/4"	NCSC-125EMT	3-1/2"	NCSC-350EMT
1-1/2"	NCSC-150EMT	4"	NCSC-400EMT

(Rigid Conduit Version Available Soon - Consult Factory)

## Prevent Injury and Save Hours

Customer must satisfy all codes and owners' specifications.



PATENT PENDING  
PATENTED



LABELS APPLY TO PRODUCTS ONLY WHERE SHOWN ABOVE

730 Pratt Boulevard • Elk Grove Village, IL 60007  
P: (847) 593-8595 • F: (847) 593-8629 • Toll-free (800) 233-8595  
E: info@spproducts.com • www.spproducts.com

**IP17**