

Nylon Wrap-Around Conduit Straps



Quickly & Firmly Secure Conduit in Seconds



- No Tools Required
- Up Thru 950 lb Load Ratings
- Flame Retardant
- Plenum Rated Up Thru 1½" Size

CAT #	ELECTRICAL			Max Load lbs.	CAT #	ELECTRICAL			Max Load lbs.
	EMT	Heavy Wall	IMC			EMT	Heavy Wall	IMC	
SPP-12-16P	N/A	N/A	N/A	170	SPP-40-44P	1-1/2" (1.740)	1-1/4" (1.660)	1-1/4" (1.638)	365
SPP-17-20P	1/2" (.706)	N/A	N/A	195	SPP-48-54P	N/A	1-1/2" (1.900)	1-1/2" (1.883)	380
SPP-21-24P	3/4" (.922)	1/2" (.840)	1/2" (.815)	215	SPP-56-63P	2" (2.197)	2" (2.375)	2" (2.360)	410
SPP-25-29P	N/A	3/4" (1.050)	3/4" (1.029)	315	SPP-66-76P	2-1/2" (2.875)	2-1/2" (2.875)	2-1/2" (2.857)	500
SPP-30-34P	1" (1.163)	1" (1.315)	1" (1.290)	320	SPP-79-93P	3" (3.500)	3" (3.500)	3" (3.476)	600
SPP-35-38P	1-1/4" (1.510)	N/A	N/A	342	SPP-101-115P	3½ & 4" (4.500)	4" (4.500)	4" (4.466)	950

NOTE: Fractional numbers reflect nominal pipe diameter, decimal numbers actual O.D. in inches.

Also Ideal for HVAC, Plumbing & Mechanical Installations

Customer must satisfy all codes and owners' specifications.



PATENT PENDING
PATENTED



LABELS APPLY TO PRODUCTS ONLY WHERE SHOWN ABOVE

730 Pratt Boulevard • Elk Grove Village, IL 60007
 P: (847) 593-8595 • F: (847) 593-8629 • Toll-free (800) 233-8595
 E: info@spproducts.com • www.spproducts.com

IP10