

Flat Fixed Position 1 Box Support Bracket



Tear drop shaped mounting holes allow fast & perfect installation of boxes without removing box screws



UL US
PATENT
PENDING



Extra width at each end for flexibility of movement between studs quickly slide left or right and fasten to studs

Openings allow installation of 4", 4^{11/16"} & 5" square boxes plus bracket makes it possible to use **Regular or Adjustable Mud Rings**

Strong 16 gauge galvanized or stainless steel

MOUNTING INSTRUCTIONS

Step 1 Align bracket center line to the stud height location required.

Step 2 Apply #8 self tapping screw pan head or Phillips to secure to stud on slots above and below slotted cross.

Step 3 Bracket can be loaded with 4", 4^{11/16"} and 5" square boxes and preassembled with boxes and mud rings required prior to installation (on stud) in prefab shop or on site.

Mud Ring Sandwiches Box to Bracket
Available with or without adjustable mud rings

Customer must satisfy all codes and owners' specifications.



PATENT PENDING
PATENTED



LABELS APPLY TO PRODUCTS ONLY WHERE SHOWN ABOVE

730 Pratt Boulevard • Elk Grove Village, IL 60007
P: (847) 593-8595 • F: (847) 593-8629 • Toll-free (800) 233-8595
E: info@spproducts.com • www.spproducts.com

IP28